


FLOOR DRYING OVEN



Internal Body & Compartment
Fully Stainless Steel (Iron Free)
Prevent Rusty & Long Run



A chimney effect that drives air upward along the center support bar, together with the oven's rectangle shape and vented shelving, allows for exceptional heat flow pattern

MODEL: FE50MS/SS(50kgs)
FE100MS/SS(100kgs)
FE150MS/SS(150kgs)
FE200MS/SS(200kgs)

Holding temperature : 150°C
Rebaking temperature : 300°C-400°C
(for 2 to 4hrs)

External - EG Mild Steel casing with Epoxy
Internal - Fully Stainless Steel (Iron Free)

A HIGH QUALITY AND DURABLE HOLDING,
REBAKING AND RECONDITIONING ELECTRODE
OVEN WITH A MILD STEEL CASING TO MAKE
REQUIREMENT FOR ALL CERTIFICATIONS OF
CALIBRATION

- Removable Shelving for use with flux and wire coils
- Even Heat Distribution – rectangle shape distributes heat by convection
- Heating Element – UL Approval
File Note UL1030 (E107991)
- Colour – safety yellow colour ensure high visibility
- Body –External Mild Steel EG
- Body –Internal Stainless Steel (Iron Free)
- Drive off moisture and get good welds.....
- Guard against rejects.....
- Eliminate rework.....
- Protect welding profits.....

Specifications

Model	FE50MS	FE100MS	FE150MS	FE200MS
Capacity	50kg	100kg	150kg	200kg
Electrode Length	457mm electrode	457mm electrode	457mm electrode	457mm electrode
Temperature	60°C - 400°C	60°C - 400°C	60°C - 400°C	60°C - 400°C
Average stabilized	Analog	Analog	Analog	Analog
Input voltage	240V AC	240V AC	240V AC	240V AC
Electrode size	10",12",14",18" (254,305,356,457mm)	10",12",14",18" (254,305,356,457mm)	10",12",14",18" (254,305,356,457mm)	10",12",14",18" (254,305,356,457mm)
Heating element	1000watts (2)	1000watts (2)	1000watts (2)	2000watts (4)
Insulation (rockfibre wool)	2" (50mm)	2" (50mm)	2" (50mm)	2" (50mm)
Shelved compartment	4	6	8	10
Inside diameter LxWxH (mm)	480x310x288mm	480x310x386mm	480x310x484mm	480x310x582mm
Outside diameter LxWxH (mm)	580x420x541mm	580x420x639mm	580x420x737mm	580x420x835mm
Nett weight	34kg	40kg	47kg	65kg
Shipping weight & Dimension L x W x H(mm)	39kg 755x520x641mm	45kg 755x520x739mm	52kg 755x520x837mm	105kg 755x520x935mm

We reserve the right to change design, material & specification without notice